

# F504

## UNDERCOUNTER DISHWASHERS

1 2

0

C

Lo TRANSPORT





## ECOMAX IT'S YOUR CHOICE! LOW PRICE HIGH PERFORMANCE

## TECHNICAL DATA, FEATURES AND DRAWINGS



The entry-level models for those who search for a low-cost dishwasher for commercial use. Ideal for startups and companies with irregular washing frequency, which invest in a dishwasher for the first time. **ecomax** meets all requirements for hygienic wash results.

### ECOMAX F504 DISHWASHER



With a high capacity of up to 60 racks per hour, this dishwasher is a reliable partner for club houses, bistros, and fast-food restaurants. The practical floor unit fits under every work counter.

#### FEATURES

- Electronic control with digital temperature indication for easy operation
- Rotating wash and rinse arms for an even water distribution
- Indented nozzles prevent blocking
- Integrated counter for cycles and water consumption, e.g. for control of water treatment system
- Deep drawn rack track for easy cleaning



www.hobartthailand.com

- USB connection for easier service access
- Incl. connection cable, supply and drain hose for immediate operation
- Thermostop function for guaranteed temperatures
- Self-cleaning programme for hygienic cleanliness also in the machine (F504-20B)
- Tank strainer reduces soiling of the tank water
- Optional cabinet base for ergonomic operation



	ECOMAX by (HOBART)	
MODELS	F504-10B	F504-12B
Cycle times*	60 / 150 sec.	60 / 150 sec.
Capacity cycles	60 /h	60 /h
Tank capacity	25 I	25 I
Water consumption	2.3 l/rack	2.3 l/rack
Wash pump	0.35 kW	0.35 kW
Tank heating	1.8 kW	1.8 kW
BOOSTER HEATING		
Standard	5.6 kW (400 V)	5.6 kW (400 V)
Alternative	1.9 kW (230 V)	1.9 kW (230 V)
TOTAL LOADING		
Standard	5.9 kW (400 V)	5.9 kW (400 V)
Alternative	2.2 kW (230 V)	2.2 kW (230 V)
Rated voltage	400/50/3N (230/50/1)	400/50/3N (230/50/1)
Width	576 mm	576 mm
Depth	604 mm	604 mm
Height	820 mm	820 mm
Loading height	360 mm	360 mm
Rack size	500 x 500 mm	500 x 500 mm

- \* The machines are equipped with an automatic cycle-time control which ensures hygienic rinse temperatures even on a cold-water supply or with reduced heating performance.
- \* Hot water connection \*\*with 230/50/1
- 60 Hz versions are available for an extra charge. (min. lot size of 5 machines)

#### made in germany


	DISHWASHER	
MODELS	F504-10B	F504-12B
Thermolabel compliant	•	•
External water treatment system**	0	0
Double walled door	•	•
Tank strainer	•	•
Drain pump	0	•
Rinse pressure pump ***	•	•
Rinse aid dispenser	•	•
Detergent dispenser	0	•
Base cabinet (435 mm high) with removable front panel	0	0
Plate rack P-18-12	•	•
Cutlery box CB-1	•	•

 For machine protection the water hardness should not exceed 3°dH, if higher we recommend using an integrated water softener or an external water treatment system.

- \*\* For use of an external water treatment system, an integrated rinse pressure pump is necessary.
- \*\*\* Flow pressure with integrated rinse pressure pump: 0,8-4 bar
- inclusive O optional

– not available

Undercounter dishwasher model F504



 ① Drain hose
 ② Supply hose
 ③ Power cord
 ④ Detergent a)
 ⑤ Rinse aid a)

 a) depending on the device chemical dispensers are not included

www.hobartthailand.com





For more information please contact Hobart Thailand dealer :

#### Or contact www.hobartthailand.com

## made in germany

The details given in this brochure are correct as of 06/2017. We reserve the right to technical or design modifications.

#### HOBART INDOCHINA OFFICE AND SPARE PARTS CENTER

HOBART Thailand 43 Thai CC Tower Building 31st FL · Room No. 310-311 South Sathorn Rd. · Yannawa Sathorn · Bangkok · 10120 · Thailand Tel: +66(0)2-675-6279-81 Fax: +66(0)2-675-6282 enquiry@hobartthailand.com www.hobartthailand.com







